Model identifier(s): Scar	15006-S FR	/FL							
Indirect heating functionality				No					
Direct heat output(kW)				4.5					
Indirect heat output(kW)				N.A					
						Emissions from space heating at nominal heat output			
			Preferred fuel	Model	PM	OGC	СО	NO _x	
Fuel				(Only one)	identifier(s)	[X] mg/Nr	n ₃ (13 %)	0 ₂)	
Wood logs with moisture content ← 25%				Yes	No	38	64	1070	99
Compressed wood with moisture content < 12%				No	No				
Other woody biomass				No	No				
Anthracite and dry steam coal				No	No				
Hard coke				No	No				
Low temperature coke				No	No				
Bituminous coal				No	No				
Lignite briquettes				No	No				
Peat briquettes				No	No				
Blended fossil fuel briquettes				No	No				
Other fossil fuel				No	No				
Blended biomass and fossil fuel briquettes				No	No				
Other blend of biomass and solid fuel				No	No				
Characteristics when operating with the preferred fuel									
Seasonal space heating energy efficiency η_s [%] 73.56									
Energy Efficiency Class				A+					
Energy Efficiency Index (E	111								
Item	Symbol	Value	Unit	It.	Symbol	ymbol Value		Unit	
Heat output				Use efficiency (NCV as re					
Nominal heat output	P _{nom}	4.5	kW	Useful efficiency at nominal heat output		$\eta_{\text{th, nom}}$			%
Minimum heat output (indicative)	P_{min}	N.A.	kW	Useful effic minimum he output (ind	$\eta_{\text{th, min}}$	N.A.		%	
Auxiliary electricity cons	Type of heat output/room temperature control (select one)								
At nominal heat output	el _{max}	x,xxx	kW	single stage temperatur					
At minimum heat output	el _{min}	x,xxx	kW	two or more	es, no l	i, no [yes/		Yes	
In standby mode	el _{SB}	x,xxx	kW	with mecha temperatur	t room [ye:		/no]		
				with electro	perature	[yes/no]			
				with electro control plus	perature	ature [yes/no]			
				with electro control plus	perature	[yes/no]			
				Other cont	nultiple sele	ctions po	ssible)		
				room temp presence d	l, with	[yes,	/no]		
				room temp open windo	l, with	[yes/no]			
			with distan	with distance control option			/no]		
Permanent pilot flame p									
Pilot flame power requirement (if applicable)	P _{pilot}	N.A.	kW			· //	1		
Name and address of the supplier: Contact details Brian Ørum, R&D Manager, Scan A/S, Denmark									